



3 Piece - 19" / 20"

| DISK TYPE> | STANDARD (A-DISK) | | | | | | | | DEEP RIM (O-DISK) | | | | | | | | Big Caliper (R-DISK) | | | | | | | |
|----------------|--------------------------------|-----|-----|-----|-----|-----|-----|-----|--------------------------------|-----|-----|-----|-----|-----|-----|-----|--------------------------------|-----|-----|-----|-----|-----|-----|-----|
| STANDARD PCD > | 5-114.3 | | | | | | | | 5-114.3 | | | | | | | | 5-114.3 | | | | | | | |
| | OFFSET RANGE AND LIP SIZE (mm) | | | | | | | | OFFSET RANGE AND LIP SIZE (mm) | | | | | | | | OFFSET RANGE AND LIP SIZE (mm) | | | | | | | |
| | 34 | 47 | 60 | 72 | 85 | 98 | 110 | 123 | 34 | 47 | 60 | 72 | 85 | 98 | 110 | 123 | 34 | 47 | 60 | 72 | 85 | 98 | 110 | 123 |
| 20 X 7.5 | +42 | +29 | +17 | +4 | | | | | +49 | +36 | +24 | +11 | | | | | +28 | +15 | +3 | -10 | | | | |
| 20 X 8.0 | +48 | +36 | +23 | +10 | -2 | | | | +55 | +43 | +30 | +17 | +5 | | | | +34 | +22 | +9 | -4 | -16 | | | |
| 20 X 8.5 | +55 | +42 | +29 | +17 | +4 | -9 | | | +62 | +49 | +36 | +24 | +11 | -2 | | | +41 | +28 | +15 | +3 | -10 | -23 | | |
| 20 X 9.0 | +61 | +48 | +36 | +23 | +10 | -2 | -15 | | +68 | +55 | +43 | +30 | +17 | +5 | -8 | | +47 | +34 | +22 | +9 | -4 | -15 | -29 | |
| 20 X 9.5 | +67 | +55 | +42 | +29 | +17 | +4 | -9 | -21 | | +62 | +49 | +36 | +24 | +11 | -2 | -14 | +53 | +41 | +28 | +15 | +3 | -10 | -23 | -35 |
| 20 X 10.0 | | +61 | +48 | +36 | +23 | +10 | -2 | -15 | | +68 | +55 | +43 | +30 | +17 | +5 | -8 | +60 | +47 | +34 | +22 | +9 | -4 | -16 | -29 |
| 20 X 10.5 | | +67 | +55 | +42 | +29 | +17 | +4 | -9 | | | +62 | +49 | +36 | +24 | +11 | -2 | +66 | +53 | +41 | +28 | +15 | +3 | -10 | -23 |
| 20 X 11.0 | | | +61 | +48 | +36 | +23 | +10 | -2 | | | +68 | +55 | +43 | +30 | +17 | +5 | | +60 | +47 | +34 | +22 | +9 | -4 | -16 |
| 20 X 11.5 | | | +67 | +55 | +42 | +29 | +17 | +4 | | | | +62 | +49 | +36 | +24 | +11 | | +66 | +53 | +41 | +28 | +15 | +3 | -10 |
| 20 X 12.0 | | | | +61 | +48 | +36 | +23 | +10 | | | | +68 | +55 | +43 | +30 | +17 | | | +60 | +47 | +34 | +22 | +9 | -4 |
| 20 X 12.5 | | | | +67 | +55 | +42 | +29 | +17 | | | | | +62 | +49 | +36 | +24 | | | | +53 | +41 | +28 | +15 | +3 |
| 20 X 13.0 | | | | | +61 | +48 | +36 | +23 | | | | | +68 | +55 | +43 | +30 | | | | | +47 | +34 | +22 | +9 |
| 20 X 13.5 | | | | | | +55 | +42 | +29 | | | | | | +62 | +49 | +36 | | | | | | +41 | +28 | +15 |
| Custom PCD> | 5H-98mm ~ 120.65mm | | | | | | | | | | | | | | | | | | | | | | | |

| DISK TYPE> | STANDARD (A-DISK) | | | | | | | | DEEP RIM (O-DISK) | | | | | | | | Big Caliper (R-DISK) | | | | | | | |
|----------------|--------------------------------|-----|-----|-----|-----|-----|-----|-----|--------------------------------|-----|-----|-----|-----|-----|-----|-----|--------------------------------|-----|-----|-----|-----|-----|-----|-----|
| STANDARD PCD > | 5-114.3 | | | | | | | | 5-114.3 | | | | | | | | 5-114.3 | | | | | | | |
| | OFFSET RANGE AND LIP SIZE (mm) | | | | | | | | OFFSET RANGE AND LIP SIZE (mm) | | | | | | | | OFFSET RANGE AND LIP SIZE (mm) | | | | | | | |
| | 34 | 47 | 60 | 72 | 85 | 98 | 110 | 123 | 34 | 47 | 60 | 72 | 85 | 98 | 110 | 123 | 34 | 47 | 60 | 72 | 85 | 98 | 110 | 123 |
| 19 X 7.5 | +45 | +32 | +20 | +7 | | | | | +52 | +39 | +27 | +14 | | | | | +28 | +15 | +3 | -10 | | | | |
| 19 X 8.0 | +51 | +39 | +26 | +13 | +1 | | | | +58 | +46 | +33 | +20 | +8 | | | | +34 | +22 | +9 | -4 | -16 | | | |
| 19 X 8.5 | +58 | +45 | +32 | +20 | +7 | -6 | | | +65 | +52 | +39 | +27 | +14 | +1 | | | +41 | +28 | +15 | +3 | -10 | -23 | | |
| 19 X 9.0 | +64 | +51 | +39 | +26 | +13 | +1 | -12 | | | +58 | +46 | +33 | +20 | +8 | -5 | | +47 | +34 | +22 | +9 | -4 | -16 | -29 | |
| 19 X 9.5 | | +57 | +45 | +32 | +20 | +7 | -6 | -18 | | +65 | +52 | +39 | +27 | +14 | +1 | -11 | +53 | +41 | +28 | +15 | +3 | -10 | -23 | -35 |
| 19 X 10.0 | | +64 | +51 | +39 | +26 | +13 | +1 | -12 | | | +58 | +46 | +33 | +20 | +8 | -5 | | +47 | +34 | +22 | +9 | -4 | -16 | -29 |
| 19 X 10.5 | | | +58 | +45 | +32 | +20 | +7 | -6 | | | +65 | +52 | +39 | +27 | +14 | +1 | | +53 | +41 | +28 | +15 | +3 | -10 | -23 |
| 19 X 11.0 | | | +64 | +51 | +39 | +26 | +13 | +1 | | | | +58 | +46 | +33 | +20 | +8 | | | +47 | +34 | +22 | +9 | -4 | -16 |
| 19 X 11.5 | | | | +58 | +45 | +32 | +20 | +7 | | | | +65 | +52 | +39 | +27 | +14 | | | | +41 | +28 | +15 | +3 | -10 |
| 19 X 12.0 | | | | | +51 | +39 | +26 | +13 | | | | | +58 | +46 | +33 | +20 | | | | | +34 | +22 | +9 | -4 |
| 19 X 12.5 | | | | | | +45 | +32 | +20 | | | | | | +52 | +39 | +27 | | | | | | +28 | +15 | +3 |
| Custom PCD> | 5H-98mm ~ 120.65mm | | | | | | | | | | | | | | | | | | | | | | | |

Standard Color: Feinheit Silver II (FS2) / Gunmetal Polish II (GMP2) / 2-Tone Metal Polish (TMP)
Optional Color: WORK Black Chrome (WBC)
Custom Color Option: Yes - Available - Please call for details

Center Cap Option: Silver / Black / Red
Valve Stem: V36 Chrome / V36 Gold
TPMS Adapability: Yes - with TPMS valve stem adapters (Sold Separately)

