

GNOSIS GR201

▲SPECIFICATIONS 22inch 2PIECE/FULL REVERSE

SIZE	STANDARD A - Disk		DEEP RIM O - Disk	
	5H-114.3(73.3) 5H-120(72.5) 5H-112(66.5) 5H-130(71.6)		5H-114.3(73.3) 5H-120(72.5) 5H-112(66.5) 5H-130(71.6)	
	(Lip Size) mm		(Lip Size) mm	
	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2
22 × 8.5J	35(45)~20(60)	19(61)~2(78)	47(45)~32(60)	31(61)~14(78)
22 × 9.0J	41(45)~14(72)	13(73)~-4(90)	53(45)~26(72)	25(73)~8(90)
22 × 9.5J	47(45)~8(84)	7(85)~-10(102)	59(45)~20(84)	19(85)~2(102)
22 × 10.0J	54(45)~1(98)	0(99)~-17(116)	66(45)~13(98)	12(99)~-5(116)
22 × 10.5J	60(45)~-5(110)	-6(111)~-23(128)	72(45)~7(110)	6(111)~-11(128)
22 × 11.0J	66(45)~-11(122)	-12(123)~-29(140)	78(45)~1(122)	0(123)~-17(140)
22 × 11.5J	73(45)~-18(136)	-19(137)~-36(154)	85(45)~-6(136)	-7(137)~-24(154)
Custom P.C.D.	5H-108~130			

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C or V39A depending on spec)
- Offset range: #1 will use V24C, #2 will use V39A
- ※ Cut anodized rim is standard

▲SPECIFICATIONS 21inch 2PIECE/REVERSE (STEP RIM)

SIZE	STANDARD A - Disk	DEEP RIM O - Disk	BIG CALIPER R - Disk
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)
	(Lip Size) mm	(Lip Size) mm	(Lip Size) mm
	Offset Range	Offset Range	Offset Range
21 × 8.5J	38(47)~0(85)	50(47)~12(85)	30(47)~-8(85)
21 × 9.0J	44(47)~-6(97)	56(47)~6(97)	36(47)~-14(97)
21 × 9.5J	50(47)~-12(109)	62(47)~0(109)	42(47)~-20(109)
21 × 10.0J	57(47)~-19(123)	69(47)~-7(123)	49(47)~-27(123)
21 × 10.5J	63(47)~-25(135)	75(47)~-13(135)	55(47)~-33(135)
21 × 11.0J	69(47)~-31(147)	81(47)~-19(147)	61(47)~-39(147)
21 × 11.5J	76(47)~-38(161)	88(47)~-26(161)	68(47)~-46(161)
21 × 12.0J	78(51)~-44(173)	90(51)~-32(173)	70(51)~-52(173)
21 × 12.5J	72(63)~-50(185)	84(63)~-38(185)	64(63)~-58(185)
Custom P.C.D.	5H-108~120.65		

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C)
- ※ Cut anodized rim is standard
- ※Please note that with lip size less than 82mm, the disk is protruding from the rim fitment portion.

▲SPECIFICATIONS 20inch 2PIECE/REVERSE (STEP RIM)

SIZE	STANDARD A - Disk	DEEP RIM O - Disk	BIG CALIPER R - Disk
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)
	(Lip Size) mm	(Lip Size) mm	(Lip Size) mm
	Offset Range	Offset Range	Offset Range
20 × 8.0J	29(49)~1(77)	41(49)~13(77)	21(49)~-7(77)
20 × 8.5J	36(49)~-6(91)	48(49)~6(91)	28(49)~-14(91)
20 × 9.0J	42(49)~-12(103)	54(49)~0(103)	34(49)~-20(103)
20 × 9.5J	48(49)~-18(115)	60(49)~-6(115)	40(49)~-26(115)
20 × 10.0J	55(49)~-25(129)	67(49)~-13(129)	47(49)~-33(129)
20 × 10.5J	61(49)~-31(141)	73(49)~-19(141)	53(49)~-39(141)
20 × 11.0J	67(49)~-37(153)	79(49)~-25(153)	59(49)~-45(153)
20 × 11.5J	74(49)~-44(167)	86(49)~-32(167)	66(49)~-52(167)
20 × 12.0J	78(51)~-50(179)	90(51)~-38(179)	70(51)~-58(179)
20 × 12.5J	72(63)~-56(191)	84(63)~-44(191)	64(63)~-64(191)
Custom P.C.D.	5H-108~120.65		

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C)
- ※ Cut anodized rim is standard
- ※Please note that with lip size less than 56mm, the disk is protruding from the rim fitment portion. (There is no protruding from the rim flange.)

GNOSIS GR201

▲ SPECIFICATIONS 20inch 2PIECE/FULL REVERSE

SIZE	STANDARD A - Disk		DEEP RIM O - Disk		BIG CALIPER R - Disk	
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	(Lip Size) mm		(Lip Size) mm		(Lip Size) mm	
	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2
20 × 8.0J	35(43)~21(57)	20(58)~-2(80)	47(43)~33(57)	32(58)~10(80)	27(43)~13(57)	12(58)~-10(80)
20 × 8.5J	42(43)~14(71)	13(72)~-9(94)	54(43)~26(71)	25(72)~3(94)	34(43)~6(71)	5(72)~-17(94)
20 × 9.0J	48(43)~8(83)	7(84)~-15(106)	60(43)~20(83)	19(84)~-3(106)	40(43)~0(83)	-1(84)~-23(106)
20 × 9.5J	54(43)~2(95)	1(96)~-21(118)	66(43)~14(95)	13(96)~-9(118)	46(43)~-6(95)	-7(96)~-29(118)
20 × 10.0J	61(43)~-5(109)	-6(110)~-28(132)	73(43)~7(109)	6(110)~-16(132)	53(43)~-13(109)	-14(110)~-36(132)
20 × 10.5J	67(43)~-11(121)	-12(122)~-34(144)	79(43)~1(121)	0(122)~-22(144)	59(43)~-19(121)	-20(122)~-42(144)
20 × 11.0J	73(43)~-17(133)	-18(134)~-40(156)	85(43)~-5(133)	-6(134)~-28(156)	65(43)~-25(133)	-26(134)~-48(156)
20 × 11.5J	80(43)~-24(147)	-25(148)~-47(170)	85(50)~-12(147)	-13(148)~-35(170)	72(43)~-32(147)	-33(148)~-55(170)
20 × 12.0J	78(51)~-30(159)	-31(160)~-53(182)	85(56)~-18(159)	-19(160)~-41(182)	70(51)~-38(159)	-39(160)~-61(182)
20 × 12.5J	72(63)~-36(171)	-37(172)~-59(194)	84(63)~-24(171)	-25(172)~-47(194)	64(63)~-44(171)	-45(172)~-67(194)
Custom P.C.D.	5H-108~120.65					

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C or V39A depending on spec)
- Offset range: #1 will use V24C, #2 will use V39A
- ※ Cut anodized rim is standard

▲ SPECIFICATIONS 19inch 2PIECE/FULL REVERSE

SIZE	STANDARD A - Disk		DEEP RIM O - Disk		BIG CALIPER R - Disk	
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	(Lip Size) mm		(Lip Size) mm		(Lip Size) mm	
	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2
19 × 7.5J	29(43)~18(54)	17(55)~-5(67)	41(43)~30(54)	29(55)~17(67)	21(43)~10(54)	9(55)~-3(67)
19 × 8.0J	35(43)~12(66)	11(67)~-1(79)	47(43)~24(66)	23(67)~11(79)	27(43)~4(66)	3(67)~-9(79)
19 × 8.5J	42(43)~5(80)	4(81)~-8(93)	54(43)~17(80)	16(81)~-4(93)	34(43)~-3(80)	-4(81)~-16(93)
19 × 9.0J	48(43)~-1(92)	-2(93)~-14(105)	60(43)~11(92)	10(93)~-2(105)	40(43)~-9(92)	-10(93)~-22(105)
19 × 9.5J	54(43)~-7(104)	-8(105)~-20(117)	66(43)~5(104)	4(105)~-8(117)	46(43)~-15(104)	-16(105)~-28(117)
19 × 10.0J	61(43)~-14(118)	-15(119)~-27(131)	73(43)~-2(118)	-3(119)~-15(131)	53(43)~-22(118)	-23(119)~-35(131)
19 × 10.5J	67(43)~-20(130)	-21(131)~-33(143)	79(43)~-8(130)	-9(131)~-21(143)	59(43)~-28(130)	-29(131)~-41(143)
19 × 11.0J	73(43)~-26(142)	-27(143)~-39(155)	85(43)~-14(142)	-15(143)~-27(155)	65(43)~-34(142)	-35(143)~-47(155)
19 × 11.5J	80(43)~-33(156)	-34(157)~-46(169)	85(50)~-21(156)	-22(157)~-34(169)	72(43)~-41(156)	-42(157)~-54(169)
19 × 12.0J	78(51)~-39(168)	-40(169)~-52(181)	85(56)~-27(168)	-28(169)~-40(181)	70(51)~-47(168)	-48(169)~-60(181)
19 × 12.5J	72(63)~-45(180)	-46(181)~-58(193)	84(63)~-33(180)	-34(181)~-46(193)	64(63)~-53(180)	-54(181)~-66(193)
Custom P.C.D.	5H-108~120.65					

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C or V39A depending on spec)
- Offset range: #1 will use V24C, #2 will use V39A
- ※ Cut anodized rim is standard