

**GNOSIS GR203**

**▲ SPECIFICATIONS 21inch 2PIECE/REVERSE (STEP RIM)**

SIZE	STANDARD		DEEP RIM		BIG CALIPER	
	A - Disk		O - Disk		R - Disk	
	5H-100(57)(60)	5H-112(66.5)	5H-100(57)(60)	5H-112(66.5)	5H-112(66.5)	
	5H-114.3(73.3)	5H-120(72.5)	5H-114.3(73.3)	5H-120(72.5)	5H-114.3(73.3)	5H-120(72.5)
	(Lip Size) mm		(Lip Size) mm		(Lip Size) mm	
	Offset Range		Offset Range		Offset Range	
21 x 8.5J	39(46)~0(85)		49(46)~10(85)		31(46)~8(85)	
21 x 9.0J	45(46)~6(97)		55(46)~4(97)		37(46)~14(97)	
21 x 9.5J	51(46)~12(109)		61(46)~2(109)		43(46)~20(109)	
21 x 10.0J	58(46)~19(123)		68(46)~9(123)		50(46)~27(123)	
21 x 10.5J	64(46)~25(135)		74(46)~15(135)		56(46)~33(135)	
21 x 11.0J	70(46)~31(147)		80(46)~21(147)		62(46)~39(147)	
21 x 11.5J	77(46)~38(161)		87(46)~28(161)		69(46)~46(161)	
21 x 12.0J	84(46)~44(173)		94(46)~34(173)		76(46)~52(173)	
21 x 12.5J	91(46)~50(185)		101(46)~40(185)		83(46)~60(185)	
Custom P.C.D.	5H-108~120.65					

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C)
- ※ Cut anodized rim is standard
- ※ Please note that with lip size less than 82mm, the disk is protruding from the rim fitment portion. (There is no protruding from the rim flange.)

**▲ SPECIFICATIONS 20inch 2PIECE/REVERSE (STEP RIM)**

SIZE	STANDARD		DEEP RIM		BIG CALIPER	
	A - Disk		O - Disk		R - Disk	
	5H-100(57)(60)	5H-112(66.5)	5H-100(57)(60)	5H-112(66.5)	5H-112(66.5)	
	5H-114.3(73.3)	5H-120(72.5)	5H-114.3(73.3)	5H-120(72.5)	5H-114.3(73.3)	5H-120(72.5)
	(Lip Size) mm		(Lip Size) mm		(Lip Size) mm	
	Offset Range		Offset Range		Offset Range	
20 x 8.0J	30(48)~1(77)		40(48)~11(77)		22(48)~7(77)	
20 x 8.5J	37(48)~6(91)		47(48)~4(91)		29(48)~14(91)	
20 x 9.0J	43(48)~12(103)		53(48)~2(103)		35(48)~20(103)	
20 x 9.5J	49(48)~18(115)		59(48)~8(115)		41(48)~26(115)	
20 x 10.0J	56(48)~25(129)		66(48)~15(129)		48(48)~33(129)	
20 x 10.5J	62(48)~31(141)		72(48)~21(141)		54(48)~39(141)	
20 x 11.0J	68(48)~37(153)		78(48)~27(153)		60(48)~45(153)	
20 x 11.5J	75(48)~44(167)		85(48)~34(167)		67(48)~52(167)	
20 x 12.0J	80(49)~50(179)		90(49)~40(179)		72(49)~58(179)	
20 x 12.5J	86(49)~56(191)		96(49)~46(191)		78(49)~64(191)	
Custom P.C.D.	5H-108~120.65					

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C)
- ※ Cut anodized rim is standard
- ※ Please note that with lip size less than 56mm, the disk is protruding from the rim fitment portion. (There is no protruding from the rim flange.)

**▲ SPECIFICATIONS 20inch 2PIECE/FULL REVERSE**

SIZE	STANDARD		DEEP RIM		BIG CALIPER	
	A - Disk		O - Disk		R - Disk	
	5H-100(57)(60)	5H-112(66.5)	5H-100(57)(60)	5H-112(66.5)	5H-112(66.5)	
	5H-114.3(73.3)	5H-120(72.5)	5H-114.3(73.3)	5H-120(72.5)	5H-114.3(73.3)	5H-120(72.5)
	(Lip Size) mm		(Lip Size) mm		(Lip Size) mm	
	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2
20 x 8.0J	36(42)~21(57)	20(58)~2(80)	46(42)~31(57)	30(58)~8(80)	28(42)~13(57)	12(58)~10(80)
20 x 8.5J	43(42)~14(71)	13(72)~9(94)	53(42)~24(71)	23(72)~1(94)	35(42)~6(71)	5(72)~17(94)
20 x 9.0J	49(42)~8(83)	7(84)~15(106)	59(42)~18(83)	17(84)~5(106)	41(42)~0(83)	-1(84)~23(106)
20 x 9.5J	55(42)~2(95)	1(96)~21(118)	65(42)~12(95)	11(96)~11(118)	47(42)~6(95)	-7(96)~29(118)
20 x 10.0J	62(42)~5(109)	-6(110)~28(132)	72(42)~5(109)	4(110)~18(132)	54(42)~13(109)	-14(110)~36(132)
20 x 10.5J	68(42)~11(121)	-12(122)~34(144)	78(42)~11(121)	-2(122)~24(144)	66(42)~25(133)	-20(122)~42(144)
20 x 11.0J	74(42)~17(133)	-18(134)~40(156)	84(42)~7(133)	-8(134)~30(156)	73(42)~32(147)	-26(134)~48(156)
20 x 11.5J	81(42)~24(147)	-25(148)~47(170)	91(42)~14(147)	-15(148)~37(170)	79(42)~38(159)	-33(148)~55(170)
20 x 12.0J	88(42)~30(159)	-31(160)~53(182)	98(42)~20(159)	-21(160)~43(182)	86(42)~46(168)	-40(160)~61(182)
20 x 12.5J	95(42)~36(171)	-37(172)~59(194)	105(42)~26(171)	-27(172)~49(194)	93(42)~52(179)	-47(172)~67(194)
Custom P.C.D.	5H-108~120.65					

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C or V39A depending on spec)
- Offset range: #1 will use V24C, #2 will use V39A
- ※ Cut anodized rim is standard

▲SPECIFICATIONS 19inch 2PIECE/FULL REVERSE

SIZE	STANDARD A - Disk		DEEP RIM O - Disk		BIG CALIPER R - Disk	
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	(Lip Size) mm		(Lip Size) mm		(Lip Size) mm	
	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2
19 x 7.5J	30(42)~18(54)	17(55)~5(67)	40(42)~28(54)	27(55)~15(67)	22(42)~10(54)	9(55)~-3(67)
19 x 8.0J	36(42)~12(66)	11(67)~-1(79)	46(42)~22(66)	21(67)~9(79)	28(42)~4(66)	3(67)~-9(79)
19 x 8.5J	43(42)~5(80)	4(81)~-8(93)	53(42)~15(80)	14(81)~2(93)	35(42)~-3(80)	-4(81)~-16(93)
19 x 9.0J	49(42)~-1(92)	-2(93)~-14(105)	59(42)~9(92)	8(93)~-4(105)	41(42)~-9(92)	-10(93)~-22(105)
19 x 9.5J	55(42)~-7(104)	-8(105)~-20(117)	65(42)~3(104)	2(105)~-10(117)	47(42)~-15(104)	-16(105)~-28(117)
19 x 10.0J	62(42)~-14(118)	-15(119)~-27(131)	72(42)~-4(118)	-5(119)~-17(131)	54(42)~-22(118)	-23(119)~-35(131)
19 x 10.5J	68(42)~-20(130)	-21(131)~-33(143)	78(42)~-10(130)	-11(131)~-23(143)	60(42)~-28(130)	-29(131)~-41(143)
19 x 11.0J	74(42)~-26(142)	-27(143)~-39(155)	84(42)~-16(142)	-17(143)~-29(155)	66(42)~-34(142)	-35(143)~-47(155)
19 x 11.5J	81(42)~-33(156)	-34(157)~-46(169)	85(48)~-23(156)	-24(157)~-36(169)	73(42)~-41(156)	-42(157)~-54(169)
19 x 12.0J	78(51)~-39(168)	-40(169)~-52(181)	85(54)~-29(168)	-30(169)~-42(181)	70(51)~-47(168)	-48(169)~-60(181)
19 x 12.5J	72(63)~-45(180)	-46(181)~-58(193)	82(63)~-35(180)	-36(181)~-48(193)	64(63)~-53(180)	-54(181)~-66(193)
Custom P.C.D.	5H-108~120.65					

- Available finishes: Matte Black (MBL) / Brush Silver Clear (BRU) / Buffing Finish (PP2) / Matte Silver (MSL) / Polished Buffing (PBU)
- Included accessories: (1) center cap / (1) valvestem (V24C or V39A depending on spec)
- Offset range: #1 will use V24C, #2 will use V39A
- ※ Cut anodized rim is standard

020817