

LS JUBILEE

▲ SPECIFICATIONS 22inch 2PIECE/FULL REVERSE

SIZE	STANDARD 5H-114.3 A - Disk		DEEP RIM 5H-114.3 O - Disk	
	Rim depth (mm)		Rim depth (mm)	
	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2
22 × 8.5J	46(52)~35(63)	34(64)~17(81)	56(52)~45(63)	44(64)~27(81)
22 × 9.0J	52(52)~29(75)	28(76)~11(93)	62(52)~39(75)	38(76)~21(93)
22 × 9.5J	58(52)~23(87)	22(88)~5(105)	68(52)~33(87)	32(88)~15(105)
22 × 10.0J	65(52)~16(101)	15(102)~-2(119)	75(52)~26(101)	25(102)~8(119)
22 × 10.5J	71(52)~10(113)	9(114)~-8(131)	81(52)~20(113)	19(114)~2(131)
22 × 11.0J	77(52)~4(125)	3(126)~-14(143)	87(52)~14(125)	13(126)~-4(143)
22 × 11.5J	84(52)~-3(139)	-4(140)~-21(157)	94(52)~7(139)	6(140)~-11(157)
Custom P.C.D.	5H-108~130			

- Available finishes: Calm Silver (CF) / Matt Black (MBL) / Super Chrome (SC)
- Included accessories: (1) center cap / (1) valvestem (V24C or V39A depending on spec)
- Offset range: #1 will use V24C, #2 will use V39A

※If the rim depth is 55mm or less, please note that the center disk will protrude beyond rim edge.

※For Custom P.C.D applications, please contact us directly so that we can assist with the lug bolt/nut type & wheel bore specification.

※Offset values can be selected from ranges shown. Offsets are available (between the two values shown) in 1mm increments.

Values shown in parentheses are the corresponding rim depth in mm.

▲ SPECIFICATIONS 21inch 2PIECE/REVERSE (STEP RIM)

SIZE	STANDARD A -Disk 5H-114.3	DEEP RIM O - Disk 5H-114.3	BIG CALIPER R - Disk 5H-114.3
	Rim depth (mm)	Rim depth (mm)	Rim depth (mm)
	Offset range	Offset range	Offset range
21 × 8.5J	63(49)~25(87)	70(49)~32(87)	46(49)~8(87)
21 × 9.0J	69(49)~19(99)	76(49)~26(99)	52(49)~2(99)
21 × 9.5J	75(49)~13(111)	82(49)~20(111)	58(49)~-4(111)
21 × 10.0J	82(49)~6(125)	89(49)~13(125)	65(49)~-11(125)
21 × 10.5J	88(49)~0(137)	95(49)~7(137)	71(49)~-17(137)
21 × 11.0J	85(58)~-6(149)	85(65)~1(149)	77(49)~-23(149)
21 × 11.5J	85(65)~-13(163)	85(72)~-6(163)	84(49)~-30(163)
21 × 12.0J	85(71)~-19(175)	85(78)~-12(175)	85(54)~-36(175)
21 × 12.5J	85(77)~-25(187)	85(84)~-18(187)	80(65)~-42(187)
Custom P.C.D.	5H-108~130		5H-108~120.65

- Available finishes: Calm Silver (CF) / Matt Black (MBL) / Super Chrome (SC)
- Included accessories: (1) center cap / (1) valvestem (V24C)

※If the rim depth is 72mm or less, please note that the center disk will protrude beyond rim edge. (There is no protruding from the rim flange)

※For Custom P.C.D applications, please contact us directly so that we can assist with the lug bolt/nut type & wheel bore specification.

※Offset values can be selected from ranges shown. Offsets are available (between the two values shown) in 1mm increments.

▲ SPECIFICATIONS 20inch 2PIECE/FULL REVERSE

SIZE	STANDARD 5H-114.3 A - Disk		DEEP RIM 5H-114.3 O-Disk		BIG CALIPER 5H-114.3 R - Disk	
	Rim depth (mm)		Rim depth (mm)		Rim depth (mm)	
	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2	Offset Range #1	Offset Range #2
20 × 8.0J	54(52)~46(60)	45(61)~23(83)	61(52)~53(60)	52(61)~30(83)	37(52)~29(60)	28(61)~6(83)
20 × 8.5J	61(52)~39(74)	38(75)~16(97)	68(52)~46(74)	45(75)~23(97)	44(52)~22(74)	21(75)~-1(97)
20 × 9.0J	67(52)~33(86)	32(87)~10(109)	74(52)~40(86)	39(87)~17(109)	50(52)~16(86)	15(87)~-7(109)
20 × 9.5J	73(52)~27(98)	26(99)~4(121)	80(52)~34(98)	33(99)~11(121)	56(52)~10(98)	9(99)~-13(121)
20 × 10.0J	80(52)~20(112)	19(113)~-3(135)	85(54)~27(112)	26(113)~4(135)	63(52)~3(112)	2(113)~-20(135)
20 × 10.5J	85(53)~14(124)	13(125)~-9(147)	85(60)~21(124)	20(125)~-2(147)	69(52)~-3(124)	-4(125)~-26(147)
20 × 11.0J	85(59)~8(136)	7(137)~-15(159)	85(66)~15(136)	14(137)~-8(159)	75(52)~-9(136)	-10(137)~-32(159)
20 × 11.5J	85(66)~1(150)	0(151)~-22(173)	85(73)~8(150)	7(151)~-15(173)	82(52)~-16(150)	-17(151)~-39(173)
20 × 12.0J	85(72)~-5(162)	-6(163)~-28(185)	85(79)~2(162)	1(163)~-21(185)	85(55)~-22(185)	-23(163)~-45(185)
20 × 12.5J	85(78)~-11(174)	-12(175)~-34(197)	85(85)~-4(174)	-5(175)~-27(197)	80(66)~-28(174)	-29(175)~-51(197)
Custom P.C.D.	5H-108~130				5H-108~120.65	

- Available finishes: Calm Silver (CF) / Matt Black (MBL) / Super Chrome (SC)
- Included accessories: (1) center cap / (1) valvestem (V24C or V39A depending on spec)
- Offset range: #1 will use V24C, #2 will use V39A

※If the rim depth is 55mm or less, please note that the center disk will protrude beyond rim edge.

※For Custom P.C.D applications, please contact us directly so that we can assist with the lug bolt/nut type & wheel bore specification.

※Offset values can be selected from ranges shown. Offsets are available (between the two values shown) in 1mm increments.

Values shown in parentheses are the corresponding rim depth in mm.