

EQUIP 40

▲SPECIFICATIONS 15inch 3PIECE/NORMAL

SIZE	STANDARD A - Disk 4H-100 4H-114.3											DEEP RIM O - Disk 4H-100 4H-114.3										
	Lip Size (mm)											Lip Size (mm)										
	45	57	70	82	95	107	120	133	145	158		45	57	70	82	95	107	120	133	145	158	
15×5.5J	3 A											13 A										
15×6.0J	10 B	-3 A										20 B	7 A									
15×6.5J	16 C	3 B	-9 A									26 C	13 B	1 A								
15×7.0J	22 D	10 C	-3 B	-16 A								32 D	20 C	7 B	-6 A							
15×7.5J	29 E	16 D	3 C	-9 B	-22 A							39 E	26 D	13 C	1 B	-12 A						
15×8.0J	35 F	22 E	10 D	-3 C	-16 B	-28 A						45 F	32 E	20 D	7 C	-6 B	-18 A					
15×8.5J	41 G	29 F	16 E	3 D	-9 C	-22 B	-35 A					51 G	39 F	26 E	13 D	1 C	-12 B	-25 A				
15×9.0J		35 G	22 F	10 E	-3 D	-16 C	-28 B	-41 A				45 G	32 F	20 E	7 D	-6 C	-18 B	-31 A				
15×9.5J			29 G	16 F	3 E	-9 D	-22 C	-35 B	-47 A				39 G	26 F	13 E	1 D	-12 C	-25 B	-37 A			
15×10.0J			22 G	10 F	-3 E	-16 D	-28 C	-41 B	-54 A				32 G	20 F	7 E	-6 D	-18 C	-31 B	-44 A			
15×10.5J				16 G	3 F	-9 E	-22 D	-35 C	-47 B					26 G	13 F	1 E	-12 D	-25 C	-37 B			
15×11.0J					10 G	-3 F	-16 E	-28 D	-41 C					20 G	7 F	-6 E	-18 D	-31 C				
15×11.5J						3 G	-9 F	-22 E	-35 D							13 G	1 F	-12 E	-25 D			
15×12.0J							-3 G	-16 F	-28 E								7 G	-6 F	-18 E			
15×12.5J								-9 G	-22 F										1 G	-12 F		
15×13.0J									-16 G												-8 G	

- Available finishes: Sprint Gold (SGL) / Brut Silver (BSL)
 - Included accessories: (1) center cap (High type or Low type) / (1) valvestem (V29A)
 - Black assembly bolts are standard
- ※ Please note with lip size of 32mm, the center cap is protruding 3mm from the rim flange