

▲SPECIFICATIONS 22inch 2PIECE/REVERSE (Step Rim)

SIZE	MIDDLE CONCAVE			DEEP CONCAVE	
	STANDARD Adisk	DEEP RIM Odisk	BIG CALIPER Rdisk	STANDARD Hdisk	DEEP RIM Wdisk
	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)
	OFFSET(LIP SIZE)mm RANGE	OFFSET(LIP SIZE)mm RANGE	OFFSET(LIP SIZE)mm RANGE	OFFSET(LIP SIZE)mm RANGE	OFFSET(LIP SIZE)mm RANGE
22 × 8.5J	26(48)~-8(82)	38(48)~-4(82)	14(48)~-20(82)	7(46)~-29(82)	21(46)~-15(82)
22 × 9.0J	32(48)~-14(94)	44(48)~-2(94)	20(48)~-26(94)	13(46)~-35(94)	27(46)~-21(94)
22 × 9.5J	38(48)~-20(106)	50(48)~-8(106)	26(48)~-32(106)	19(46)~-41(106)	33(46)~-27(106)
22 × 10.0J	45(48)~-27(120)	57(48)~-15(120)	33(48)~-39(120)	26(46)~-48(120)	40(46)~-34(120)
22 × 10.5J	51(48)~-33(132)	63(48)~-21(132)	39(48)~-45(132)	32(46)~-54(132)	46(46)~-40(132)
22 × 11.0J	57(48)~-39(144)	69(48)~-27(144)	45(48)~-51(144)	38(46)~-60(144)	52(46)~-46(144)
22 × 11.5J	64(48)~-46(158)	76(48)~-34(158)	52(48)~-58(158)	45(46)~-67(158)	59(46)~-53(158)
22 × 12.0J	67(51)~-52(170)	79(51)~-40(170)	55(51)~-64(170)	46(51)~-73(170)	60(51)~-59(170)
22 × 12.5J	61(63)~-58(182)	73(63)~-46(182)	49(63)~-70(182)	39(64)~-79(182)	53(64)~-65(182)
PCD RANGE	5H-108~120.65				

●STANDARD COLOR: MAT BLACK(MBL) / MAT SILVER(MSL) / BRUSHED(BRU)

CVSM-SR-HRN

/ COMPOSITE BUFFED & BRUSHED(PBU) / BUFF FINISH(PP2)

CVSD-SR-HRN

●INCLUDED ACCESORIES : CENTER CAP/1PC-VALVE STEM/1PC(V24C)

※STANDARD BARREL FINISH: BUFF ANODIZED(D)

※MIDDLE CONCAVE: THE SPOKE END COMES OUT OF RIM JOINT WHEN THE LIP SIZE IS LESS THAN 76MM.

DEEP CONCAVE: THE SPOKE END COMES OUT OF RIM JOINT WHEN THE LIP SIZE IS LESS THAN 79MM

(IT WON'T COME OUT OF RIM FLANGE.)

▲SPECIFICATIONS 21inch 2PIECE/FULL REVERSE

SIZE	MIDDLE CONCAVE					
	STANDARD Adisk		DEEP RIM Odisk		BIG CALIPER Rdisk	
	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	OFFSET(LIP SIZE)mm		OFFSET(LIP SIZE)mm		OFFSET(LIP SIZE)mm	
OFFSET RANGE: 1	OFFSET RANGE: 2	OFFSET RANGE: 1	OFFSET RANGE: 2	OFFSET RANGE: 1	OFFSET RANGE: 2	
21 × 8.5J	36(38)~-14(60)	13(61)~-4(78)	48(38)~-26(60)	25(61)~-8(78)	24(38)~-2(60)	1(61)~-16(78)
21 × 9.0J	42(38)~-8(72)	7(73)~-10(90)	54(38)~-20(72)	19(73)~-2(90)	30(38)~-4(72)	-5(73)~-22(90)
21 × 9.5J	48(38)~-2(84)	1(85)~-16(102)	60(3)~14(84)	13(85)~-4(102)	36(38)~-10(84)	-11(85)~-28(102)
21 × 10.0J	55(38)~-5(98)	-6(99)~-23(116)	67(38)~-7(98)	6(99)~-11(116)	43(38)~-17(98)	-18(99)~-35(116)
21 × 10.5J	61(38)~-11(110)	-12(111)~-29(128)	73(38)~-1(110)	0(111)~-17(128)	49(38)~-23(110)	-24(111)~-41(128)
21 × 11.0J	67(38)~-17(122)	-18(123)~-35(140)	79(38)~-5(122)	-6(123)~-23(140)	55(38)~-29(122)	-30(123)~-47(140)
21 × 11.5J	73(39)~-24(136)	-25(137)~-42(154)	85(39)~-12(136)	-13(137)~-30(154)	61(39)~-36(136)	-37(137)~-54(154)
PCD RANGE	5H-108~120.65					

SIZE	DEEP CONCAVE			
	STANDARD Hdisk		DEEP RIM Wdisk	
	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	OFFSET(LIP SIZE)mm		OFFSET(LIP SIZE)mm	
OFFSET RANGE: 1	OFFSET RANGE: 2	OFFSET RANGE: 1	OFFSET RANGE: 2	
21 × 8.5J	11(42)~-8(61)	-9(62)~-26(79)	25(42)~-6(61)	5(62)~-12(79)
21 × 9.0J	17(42)~-14(73)	-15(74)~-32(91)	31(42)~-0(73)	-1(74)~-18(91)
21 × 9.5J	23(42)~-20(85)	-21(86)~-38(103)	37(42)~-6(85)	-7(86)~-24(103)
21 × 10.0J	30(42)~-27(99)	-28(100)~-45(117)	44(42)~-13(99)	-14(100)~-31(117)
21 × 10.5J	36(42)~-33(111)	-34(112)~-51(129)	50(42)~-19(111)	-20(112)~-37(129)
21 × 11.0J	42(42)~-39(123)	-40(124)~-57(141)	56(42)~-25(123)	-26(124)~-43(141)
21 × 11.5J	49(42)~-46(137)	-47(138)~-64(155)	63(42)~-32(137)	-33(138)~-50(155)
PCD RANGE	5H-108~120.65			

CVSD-HRN

●STANDARD COLOR: MAT BLACK(MBL) / MAT SILVER(MSL) / BRUSHED(BRU)

/ COMPOSITE BUFFED & BRUSHED(PBU) / BUFF FINISH(PP2)

●INCLUDED ACCESORIES : CENTER CAP/1PC-VALVE STEM/1PC(V24C/V39A)

INSET RANGE:1=V24C. INSET RANGE:2=V39A

※STANDARD BARREL FINISH: BUFF ANODIZED(D)

▲SPECIFICATIONS 21inch 2PIECE/REVERSE (Step Rim)

SIZE	MIDDLE CONCAVE			DEEP CONCAVE	
	STANDARD Adisk	DEEP RIM Odisk	BIG CALIPER Rdisk	STANDARD Hdisk	DEEP RIM Wdisk
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-114.3(73.3) 5H-120(72.5)	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)
	OFFSET(LIP SIZE)mm	OFFSET(LIP SIZE)mm	OFFSET(LIP SIZE)mm	OFFSET(LIP SIZE)mm	OFFSET(LIP SIZE)mm
	OFFSET RANGE	OFFSET RANGE	OFFSET RANGE	OFFSET RANGE	OFFSET RANGE
21 × 8.5J	27(45)~-13(85)	39(45)~-1(85)	19(45)~-21(85)	7(46)~-32(85)	21(46)~-18(85)
21 × 9.0J	33(45)~-19(97)	45(45)~-7(97)	25(45)~-27(97)	13(46)~-38(97)	27(46)~-24(97)
21 × 9.5J	39(45)~-25(109)	51(45)~-13(109)	31(45)~-33(109)	19(46)~-44(109)	33(46)~-30(109)
21 × 10.0J	46(45)~-32(123)	58(45)~-20(123)	38(45)~-40(123)	26(46)~-51(123)	40(46)~-37(123)
21 × 10.5J	52(45)~-38(135)	64(45)~-26(135)	44(45)~-46(135)	32(46)~-57(135)	46(46)~-43(135)
21 × 11.0J	58(45)~-44(147)	70(45)~-32(147)	50(45)~-52(147)	38(46)~-63(147)	52(46)~-49(147)
21 × 11.5J	65(45)~-51(161)	77(45)~-39(161)	57(45)~-59(161)	45(46)~-70(161)	59(46)~-56(161)
21 × 12.0J	65(51)~-57(173)	77(51)~-45(173)	57(51)~-65(173)	46(51)~-76(173)	60(51)~-62(173)
21 × 12.5J	59(63)~-63(185)	71(63)~-51(185)	51(63)~-71(185)	39(64)~-82(185)	53(64)~-68(185)
PCD RANGE	5H-108~120.65				

●STANDARD COLOR: MAT BLACK(MBL) / MAT SILVER(MSL) / BRUSHED(BRU)

/ COMPOSITE BUFFED & BRUSHED(PBU) / BUFF FINISH(PP2)

●INCLUDED ACCESSORIES: CENTER CAP/1PC-VALVE STEM/1PC(V24C)

※STANDARD BARREL FINISH: BUFF ANODIZED(D)

※MIDDLE CONCAVE: THE SPOKE END COMES OUT OF RIM JOINT WHEN THE LIP SIZE IS LESS THAN 74MM.

DEEP CONCAVE: THE SPOKE END COMES OUT OF RIM JOINT WHEN THE LIP SIZE IS LESS THAN 80MM

(IT WON'T COME OUT OF RIM FLANGE.)

▲SPECIFICATIONS 20inch 2PIECE/FULL REVERSE

SIZE	MIDDLE CONCAVE					
	STANDARD Adisk		DEEP RIM Odisk		BIG CALIPER Rdisk	
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	OFFSET(LIP SIZE)mm		OFFSET(LIP SIZE)mm		OFFSET(LIP SIZE)mm	
	OFFSET RANGE: 1	OFFSET RANGE: 2	OFFSET RANGE: 1	OFFSET RANGE: 2	OFFSET RANGE: 1	OFFSET RANGE: 2
20 × 8.0J	31(35)~-9(57)	8(58)~-14(80)	43(35)~-21(57)	20(58)~-2(80)	23(35)~-1(57)	0(58)~-22(80)
20 × 8.5J	38(35)~-2(71)	1(72)~-21(94)	50(35)~-14(71)	13(72)~-9(94)	30(35)~-6(71)	-7(72)~-29(94)
20 × 9.0J	44(35)~-4(83)	-5(84)~-27(106)	56(35)~-8(83)	7(84)~-15(106)	36(35)~-12(83)	-13(84)~-35(106)
20 × 9.5J	50(35)~-10(95)	-11(96)~-33(118)	62(35)~-2(95)	1(96)~-21(118)	42(35)~-18(95)	-19(96)~-41(118)
20 × 10.0J	57(35)~-17(109)	-18(110)~-40(132)	69(35)~-5(109)	-6(110)~-28(132)	49(35)~-25(109)	-26(110)~-48(132)
20 × 10.5J	63(35)~-23(121)	-24(122)~-46(144)	75(35)~-11(121)	-12(122)~-34(144)	55(35)~-31(121)	-32(122)~-54(144)
20 × 11.0J	69(35)~-29(133)	-30(134)~-52(156)	81(35)~-17(133)	-18(134)~-40(156)	61(35)~-37(133)	-38(134)~-60(156)
20 × 11.5J	71(40)~-36(147)	-37(148)~-59(170)	83(40)~-24(147)	-25(148)~-47(170)	63(40)~-44(147)	-45(148)~-67(170)
20 × 12.0J	65(52)~-42(159)	-43(160)~-65(182)	77(52)~-30(159)	-31(160)~-53(182)	57(52)~-50(159)	-51(160)~-73(182)
20 × 12.5J	59(64)~-48(171)	-49(172)~-71(194)	71(64)~-36(171)	-37(172)~-59(194)	51(64)~-56(171)	-57(172)~-79(194)
PCD RANGE	5H-108~120.65					

SIZE	DEEP CONCAVE			
	STANDARD Hdisk		DEEP RIM Wdisk	
	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	OFFSET(LIP SIZE)mm		OFFSET(LIP SIZE)mm	
	OFFSET RANGE: 1	OFFSET RANGE: 2	OFFSET RANGE: 1	OFFSET RANGE: 2
20 × 8.0J	6(41)~-11(58)	-12(59)~-34(81)	20(41)~-3(58)	2(59)~-20(81)
20 × 8.5J	13(41)~-18(72)	-19(73)~-41(95)	27(41)~-4(72)	-5(73)~-27(95)
20 × 9.0J	19(41)~-24(84)	-25(85)~-47(107)	33(41)~-10(84)	-11(85)~-33(107)
20 × 9.5J	25(41)~-30(96)	-31(97)~-53(119)	39(41)~-16(96)	-17(97)~-39(119)
20 × 10.0J	32(41)~-37(110)	-38(111)~-60(133)	46(41)~-23(110)	-24(111)~-46(133)
20 × 10.5J	38(41)~-43(122)	-44(123)~-66(145)	52(41)~-29(122)	-30(123)~-52(145)
20 × 11.0J	44(41)~-49(134)	-50(135)~-72(157)	58(41)~-35(134)	-36(135)~-58(157)
20 × 11.5J	51(41)~-56(148)	-57(149)~-79(171)	65(41)~-42(148)	-43(149)~-65(171)
20 × 12.0J	46(52)~-62(160)	-63(161)~-85(183)	60(52)~-48(160)	-49(161)~-71(183)
20 × 12.5J	39(65)~-68(172)	-69(173)~-91(195)	53(65)~-54(172)	-55(173)~-77(195)
PCD RANGE	5H-108~120.65			

●STANDARD COLOR: MAT BLACK(MBL) / MAT SILVER(MSL) / BRUSHED(BRU)

/ COMPOSITE BUFFED & BRUSHED(PBU) / BUFF FINISH(PP2)

●INCLUDED ACCESSORIES: CENTER CAP/1PC-VALVE STEM/1PC(V24C/V39A)

INSET RANGE:1=V24C, INSET RANGE:2=V39A

※STANDARD BARREL FINISH: BUFF ANODIZED(D)

CVSD+HRH

▲SPECIFICATIONS 20inch 2PIECE/REVERSE (Step Rim)

SIZE	MIDDLE CONCAVE		DEEP CONCAVE	
	STANDARD Adisk	DEEP RIM Odisk	STANDARD Hdisk	DEEP RIM Wdisk
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	5H-114.3(73.3) 5H-120(72.5)	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)
	OFFSET (LIP SIZE)mm	OFFSET (LIP SIZE)mm	OFFSET (LIP SIZE)mm	OFFSET (LIP SIZE)mm
	OFFSET RANGE	OFFSET RANGE	OFFSET RANGE	OFFSET RANGE
20 x 8.0J	26(48)~-2(76)	38(48)~-10(76)	-	-
20 x 8.5J	33(48)~-9(90)	45(48)~-3(90)	20(49)~-22(91)	28(49)~-14(91)
20 x 9.0J	39(48)~-15(102)	51(48)~-3(102)	26(49)~-28(103)	34(49)~-20(103)
20 x 9.5J	45(48)~-21(114)	57(48)~-9(114)	32(49)~-34(115)	40(49)~-26(115)
20 x 10.0J	52(48)~-28(128)	64(48)~-16(128)	39(49)~-41(129)	47(49)~-33(129)
20 x 10.5J	58(48)~-34(140)	70(48)~-22(140)	45(49)~-47(141)	53(49)~-39(141)
20 x 11.0J	64(48)~-40(152)	76(48)~-28(152)	51(49)~-53(153)	59(49)~-45(153)
20 x 11.5J	70(49)~-47(166)	82(49)~-35(166)	58(49)~-60(167)	66(49)~-52(167)
20 x 12.0J	74(51)~-53(178)	85(52)~-41(178)	61(52)~-66(179)	69(52)~-58(179)
20 x 12.5J	67(64)~-59(190)	79(64)~-47(190)	55(64)~-72(191)	63(64)~-64(191)
PCD RANGE	5H-108~120.65			

●STANDARD COLOR: MAT BLACK(MBL) / MAT SILVER(MSL) / BRUSHED(BRU)

/ COMPOSITE BUFFED & BRUSHED(PBU) / BUFF FINISH(PP2)

●INCLUDED ACCESSORIES : CENTER CAP/1PC-VALVE STEM/1PC(V24C)

※STANDARD BARREL FINISH: BUFF ANODIZED(D)

※MIDDLE CONCAVE: THE SPOKE END COMES OUT OF RIM JOINT WHEN THE LIP SIZE IS LESS THAN 76MM.

DEEP CONCAVE: THE SPOKE END COMES OUT OF RIM JOINT WHEN THE LIP SIZE IS LESS THAN 83MM

(IT WON'T COME OUT OF RIM FLANGE.)

▲SPECIFICATIONS 19inch 2PIECE/FULL REVERSE

SIZE	MIDDLE CONCAVE			
	STANDARD Adisk		DEEP RIM Odisk	
	5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	OFFSET (LIP SIZE)mm		OFFSET (LIP SIZE)mm	
	OFFSET RANGE : 1	OFFSET RANGE : 2	OFFSET RANGE : 1	OFFSET RANGE : 2
19 x 7.5J	30(38)~14(54)	13(55)~1(67)	42(38)~26(54)	25(55)~13(67)
19 x 8.0J	36(38)~8(66)	7(67)~-5(79)	48(38)~20(66)	19(67)~7(79)
19 x 8.5J	43(38)~1(80)	-0(81)~-12(93)	55(38)~13(80)	12(81)~0(93)
19 x 9.0J	49(38)~-5(92)	-6(93)~-18(105)	61(38)~7(92)	6(93)~-6(105)
19 x 9.5J	55(38)~-11(104)	-12(105)~-24(117)	67(38)~1(104)	0(105)~-12(117)
19 x 10.0J	62(38)~-18(118)	-19(119)~-31(131)	74(38)~-6(118)	-7(119)~-19(131)
19 x 10.5J	68(38)~-24(130)	-25(131)~-37(143)	80(38)~-12(130)	-13(131)~-25(143)
19 x 11.0J	74(38)~-30(142)	-31(143)~-43(155)	85(39)~-18(142)	-19(143)~-31(155)
19 x 11.5J	80(39)~-37(156)	-38(157)~-50(169)	85(46)~-25(156)	-26(157)~-38(169)
19 x 12.0J	74(51)~-43(168)	-44(169)~-56(181)	85(52)~-31(168)	-32(169)~-44(181)
19 x 12.5J	67(64)~-49(180)	-50(181)~-62(193)	79(64)~-37(180)	-38(181)~-50(193)
PCD RANGE	5H-108~120.65			
SIZE	DEEP CONCAVE			
	STANDARD Hdisk		DEEP RIM Wdisk	
	5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)		5H-100(57)(60) 5H-112(66.5) 5H-114.3(73.3) 5H-120(72.5)	
	OFFSET (LIP SIZE)mm		OFFSET (LIP SIZE)mm	
	OFFSET RANGE : 1	OFFSET RANGE : 2	OFFSET RANGE : 1	OFFSET RANGE : 2
19 x 7.5J				
19 x 8.0J	15(47)~-5(67)	-16(68)~-18(80)	23(47)~3(67)	2(68)~-10(80)
19 x 8.5J	22(47)~-12(81)	-13(82)~-25(94)	30(47)~-4(81)	-5(82)~-17(94)
19 x 9.0J	28(47)~-18(93)	-19(94)~-31(106)	36(47)~-10(93)	-11(94)~-23(106)
19 x 9.5J	34(47)~-24(105)	-25(106)~-37(118)	42(47)~-16(105)	-17(106)~-29(118)
19 x 10.0J	41(47)~-31(119)	-32(120)~-44(132)	49(47)~-23(119)	-24(120)~-36(132)
19 x 10.5J	47(47)~-37(131)	-38(132)~-50(144)	55(47)~-29(131)	-30(132)~-42(144)
19 x 11.0J	53(47)~-43(143)	-44(144)~-56(156)	61(47)~-35(143)	-36(144)~-48(156)
19 x 11.5J	60(47)~-50(157)	-51(158)~-63(170)	68(47)~-42(157)	-43(158)~-55(170)
19 x 12.0J	61(52)~-56(169)	-57(170)~-69(182)	69(52)~-48(169)	-49(170)~-61(182)
19 x 12.5J	55(64)~-62(181)	-63(182)~-75(194)	63(64)~-54(181)	-55(182)~-67(194)
PCD RANGE	5H-108~120.65			

●STANDARD COLOR: MAT BLACK(MBL) / MAT SILVER(MSL) / BRUSHED(BRU)

/ COMPOSITE BUFFED & BRUSHED(PBU) / BUFF FINISH(PP2)

●INCLUDED ACCESSORIES : CENTER CAP/1PC-VALVE STEM/1PC(V24C/V39A)

INSET RANGE:1=V24C, INSET RANGE:2=V39A

※STANDARD BARREL FINISH: BUFF ANODIZED(D)